1-ELLING TRAILERS

HYDRAULIC DUMP TRAILERS

DT, DT HD, DO DT, E SD

Trailers Shown Below: FT-6 DT 32174, FT-14 DT HD 37868-LAE, FT-16-2 DT 60130-BOO





The *I-ELLING* Style

Quality ~ Craftsmanship ~ Pride



Since 1974

DT-105

DROP DECK DUMP SERIES

DT SERIES

- Load capacities ranging from 4,500 lbs. to 7,000 lbs.
- 10-gauge steel floor with 20" high 12-gauge sides
- Deck width: FT-6 DT 60" ID, FT-10 DT 80" ID
- Single hydraulic cylinder
- Double-acting spreader gate
- Tie downs stake pockets
- Heavy-duty battery, pump, and remote with 15 ft. cord



- Load capacities ranging from 9,900 lbs. to 13,600 lbs.
- 10 gauge steel floor with 20" high 12 gauge sides FT-12 &14 DT
 7 gauge steel floor with 20" high 10 gauge sides FT-16 DT
- Deck width 80" ID, 102" OD
- Heavy-duty TAFCO 10 ton scissor hoist -FT-12 DT & FT-14 DT (12')
 Heavy-duty TAFCO 15 - ton scissor hoist -FT-14 DT (14' & 16') & FT-16 DT
- 5' 5" slide-out ramps with storage under deck
- Double rear swing-out doors
- Tie downs stake pockets and D-rings
- Heavy-duty battery, pump, and remote with 15 ft. cord



FT-6 DT - shown with optional hydraulic surge brakes & gas engine (in lieu of electric/hydraulic pump) 39504



FT-14 DT HD - standard slide-out ramps store under deck 37668-LAE

DT SP (STATIONARY PLATFORM)



The Stationary Platform Option can be selected on any of Felling's Hydraulic Dump Model Lines.

- Stationary deck: pressure treated wood
- Ramp 48" long flip-up spring assist ramp

ESD (SIDE DUMP)



FT-14 E SD - shown with optional floor plate rear deck, spare wheel & tire mounted 32800

- Load capacities ranging from 12,000 lbs. to 16,000 lbs.
- Dump box: 10-ga. steel floor with 20" high 12-ga. sides
- Rear deck: pressure treated wood w/split full width ramps
- Deck width 80" ID

- Single hydraulic cylinder
- Double-acting spreader gate
- Tie downs stake pockets & D-rings
- Heavy-duty battery, pump, and remote with 15 ft. cord

Spreader Gate with Landscape Gate (galvanized unit shown)





Double Rear Swing-out Gate









Grain Door with Shoot in End Gate



DECK OVER DUMP SERIES DT DO SERIES

- Load capacities ranging from 10,000 lbs. to 14,000 lbs.
- 10 gauge steel floor with 20" high 12 gauge sides
- Deck width: 96" OD, 88" ID
- Heavy-duty TAFCO 10 ton scissor hoist FT-12-2 DT & FT-14-2 DT (12') Heavy-duty TAFCO 15 - ton scissor hoist - FT-14-2 DT (14' & 16') & FT-16-2 DT
- Double-acting spreader gate
- Tie downs stake pockets
- Heavy-duty battery, pump, and remote with 15 ft. cord



FT-16-2 DT DO

DT DO (CONTRACTOR BODY) SERIES

- Load capacities ranging from 18,000 lbs. to 26,000 lbs.
- Contractor body with 14" high hinged, fold down sides
- 7 gauge steel floor with 10 gauge sides
- Deck width 102" OD, 88" ID
- · Heavy-duty TAFCO 20-ton scissor hoist
- 20" Double-acting spreader gate
- Tie downs stake pockets
- Heavy-duty battery, pump, and remote with 15 ft. cord



FT-18-2 DT DO Contractor Body standard fold down sides

DT DO (CONSTRUCTION BODY) SERIES

- · Load capacities ranging from 12,000 lbs. to 26,000 lbs.
- 7 gauge steel floor with 14" high 10 gauge sides
- Optional side heights: 30", 36", and 48"
- Deck width 98" OD, 92" ID
- Heavy-duty TAFCO 20-ton scissor hoist FT-20-2 DT -FT-30-2 DT
- 20" Double-acting spreader gate
- Tie downs stake pockets
- Heavy-duty battery, pump, and remote with 15 ft. cord



FT-30-2 DT DO Construction Body - shown with optional gooseneck coupler & tie rail around dump box

Double Rear Spreader Gate





Hydraulic Jack



Side Drop Door



Bolt on Tarp Kit with Aluminum Shroud





HOT DIP GALVANIZING AVAILABLE ON ALL MODELS.

TIOT DIP GALVANIZING AVAILABLE ON ALL IVIODELS.											
Dump Trailer Specifications	Deck Length	Deck Construction	Trailer Weight (Approx.)	Box Capacity	Deck Height (loaded)	Wheels & Tires	Cylinder / Hoist	Dump Angle (loaded)	Dump Gate	Jack	GVWR (lbs.)
DT SERIES											
FT-6 DT	8'	10 ga. steel w/ 20" high 12 ga. sides	2,500 lbs. / 1,133 kg.	2.5 yds. 498 gal.	21"	ST235/80R16 E, 8 bolt	Single Hydraulic Cyl.	45°	Double-Acting Spreader Gate	7K	7,000 lbs.
FT-10 DT	10'	10 ga. steel w/ 20" high 12 ga. sides	2,980 lbs. / 1,351 kg.	4.1 yds. 831 gal.	22"	ST225/75R15 D, 6 bolt	Single Hyd. Cyl. (14' length - twin Cylinders)	45°	Double-Acting Spreader Gate	7K	9,980 lbs. *
DT-HD SERIES (HEAVY DUTY)											
FT-12 DT HD	12'	10 ga. steel w/ 20" high 12 ga. sides	3,900 lbs. / 1,769 kg.	4.9 yds. 997 gal.	22"	ST235/80R16 E, 8 bolt	HD 10 Ton Scissor Hoist	45°	Double Rear Swing-Out Doors	12K	13,800 lbs.
FT-14 DT HD	12'	10 ga. steel w/ 20" high 12 ga. sides	4,200 lbs. / 1,905 kg.	4.9 yds. 997 gal.	22"	ST235/80R16 E, 8 bolt	HD 10 Ton Scissor Hoist, 14' & 16' HD 15 Ton Scissor Hoist	45°	Double Rear Swing-Out Doors	12K	16,100 lbs.
FT-16 DT HD	12'	7 ga. steel w/ 20" high 10 ga. sides	4,800 lbs. / 2,177 kg.	4.9 yds. 997 gal.	24"	215/75R17.5 H, 8 bolt	HD 15 Ton Scissor Hoist	45°	Double Rear Swing-Out Doors	12K	18,400 lbs.
DT-DO SERIES (DECK-OVER)											
FT-12-2 DT	12'	10 ga. steel w/ 20" high 12 ga. sides	4,000 lbs. / 1,814 kg.	4.9 yds. 997 gal.	36"	ST235/80R16 E, 8 bolt	HD 10 Ton Scissor Hoist	45°	Double-Acting Spreader Gate	12K	14,000 lbs.
FT-14-2 DT	12'	10 ga. steel w/20" high 12 ga. sides	4,400 lbs. / 1,995 kg.	4.9 yds. 997 gal.	36"	ST235/80R16 E, 8 bolt	HD 10 Ton Scissor Hoist, HD 15 Ton Scissor Hoist 14' & 16'	45°	Double-Acting Spreader Gate	12K	16,400 lbs.
FT-16-2 DT	14'	7 ga. steel w/ 20" high 10 ga. sides	5,300 lbs. / 2,404 kg.	5.8 yds. 1,163 gal.	38"	215/75R17.5 H, 8 bolt	HD 15 Ton Scissor Hoist	45°	Double-Acting Spreader Gate	12K	19,300 lbs.
FT-20-2 DT	14'	Contractor Body w/14" high hinged sides	5,900 lbs. / 2,676 kg.	4.0 yds. 814 gal.	38"	ST235/80R16 E, 8 bolt	HD 20 Ton Scissor Hoist	45°	Double-Acting Spreader Gate	12K	23,900 lbs.
FT-24-2 DT	14'	Contractor Body w/14" high hinged sides	7,400 lbs. / 3,356 kg.	4.0 yds. 814 gal.	38"	ST235/80R16 E, 8 bolt	HD 20 Ton Scissor Hoist	45°	Double-Acting Spreader Gate	12K	28,400 lbs.
FT-30-2 DT	14'	Contractor Body w/14" high hinged sides	8,000 lbs. / 3,628 kg.	4.0 yds. 814 gal.	40"	215/75R17.5, 8 bolt	HD 20 Ton Scissor Hoist	45°	Double-Acting Spreader Gate	12K	34,000 lbs.
E SD SERIES (SIDE DUMP) DUMP BOX 5' X 8'											
FT-12 E SD	14'	10 ga. steel w/20" high 12 ga. sides	3,500 lbs. / 1,587 kg.	2.0 yds. 399 gal.	24"	ST235/80R16 E, 8 bolt	Single Hyd. Cylinder	45°	Double-Acting Spreader Gate	12K	13,800 lbs.
FT-14 E SD	14'	10 ga. steel w/20" high 12 ga. sides	4,000 lbs. / 1,814 kg.	2.0 yds. 399 gal.	24"	ST235/80R16 E, 8 bolt	Single Hyd. Cylinder	45°	Double-Acting Spreader Gate	12K	16,100 lbs.
FT-16 E SD	18'	10 ga. steel w/20" high 12 ga. sides	4,000 lbs. / 1,814 kg.	2.0 yds. 399 gal.	24"	215/75R17.5, 8 bolt	Single Hyd. Cylinder	45°	Double-Acting Spreader Gate	12K	18,400 lbs.

^{*} FT-10 DT - GVWR of 12,980 with conspicuity tape option

To learn more about us, have us mail you a specific full color brochure, or locate our nearest Felling Dealer, go to www.felling.com or give us a call at 1-800-245-2809.

Your **FELLING** TRAILERS Dealer:



Join Us Online

f 📒 You Tube

Manufactured & Distributed by: **Felling Trailers, Inc.** 1525 Main St. S. • Sauk Centre, MN 56378 (320) 352-5239 • (320) 352-5230 FAX

Visit us online at www.felling.com E-mail us at: trailers@felling.com

Call 1-800-245-2809

for your nearest dealer.



^{**} Additional lengths available • Measurements are approximate • Some models may be shown with optional equipment • All specifications are subject to change