

# AlphaBlower™ Specifications



**AlphaBlower 24-84-H**  
Hydraulic Flow: 30-45 GPM



**AlphaBlower 24-84-P**  
PTO Power: 75-130 HP



**AlphaBlower 33-100-H**  
Hydraulic Flow: 40-50 GPM



**AlphaBlower 33-100-P**  
PTO Power: 100-250 HP



**AlphaBlower 36-106-P**  
PTO Power: 150-350 HP

Model Number	24-84-H	24-84-P	33-100-H	33-100-P	36-106-P
Width of Auger (cm)	85" (216)	85" (216)	100" (254)	100" (254)	106" (269)
Overall Width at Drift Breakers (cm)	90" (229)	90" (229)	106.5" (271)	106.5" (271)	111" (282)
Center Cutting Height (cm)	36" (91)	36" (91)	41" (104)	41" (104)	46" (117)
Side Cutting Height (cm)	57" (145)	57" (145)	75" (191)	75" (191)	75" (190)
Impeller Diameter (cm)	24" (61)	24" (61)	33" (84)	33" (84)	36" (91)
Impeller Depth (cm)	9" (23)	9" (23)	11" (28)	11" (28)	14" (36)
Auger Diameter (cm)	28" (71)	28" (71)	33" (84)	33" (84)	38" (97)
Weight (kg)	2,400 lbs (1,089)	2,050 lbs (930)	3,900 lbs (1,769)	3,650 lbs (1,656)	4,120 lbs (1,869)
Min. Three-Point Hitch Lift Capacity (kg)	N/A	3,450 lbs (1,565)	N/A	5,500 lbs (2,495)	6,800 lbs (3,084)
Hardox 500 Reversible Cutting Edges (cm)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)	½" x 8" (1.2 x 12)
Hardox 500 Side Skids	Standard	Standard	Standard	Standard	Standard
Hardox Impeller Housing	Standard	Standard	Standard	Standard	Standard
Auto Reset Hydraulic Cut-Out Clutch(es)	Standard (2)	Standard (1)	Standard (2)	Standard (2)	Standard (1)
HD Upper Wing Edges (Drift Breakers)	Standard	Standard	Standard	Standard	Standard
Screw Adjustable Gauge Wheels	Optional	N/A	Standard	N/A	Optional
Hydraulic Chute Rotation	Standard	Standard	Standard	Standard	Standard
Deluxe HD Chute	4-Flap	4-Flap	4-Flap	4-Flap	4-Flap
Hydraulically Collapsible Chute	Optional	N/A	Standard	N/A	Optional
HD Truck Loading Chute	Optional	Optional	Optional	Optional	Optional
PTO Stub Shaft Diameter	N/A	1-3/4"	N/A	1-3/4"	1-3/4"
PTO	N/A	1,000 rpm	N/A	1,000 rpm	1,000 rpm
PTO Shaft Included	Standard	N/A	Standard	Standard	N/A
Recommended GPM (LPM)	30-45 (114-170)	N/A	40-50 (150-190)	N/A	N/A
Recommended PTO HP	N/A	75 - 130	N/A	100 - 250	150 - 350
To Fit Rear Mount PTO	N/A	Standard	N/A	Standard	Standard
To Fit Rear Mount PTO (Towing Position)	N/A	N/A	N/A	Add FMT-33100 Option	N/A