

SnowPlow Specifications



FlexFlow™
2,000-6,000 lbs.



UltraPlow™
6,000-10,000 lbs.



UltraPlowXT™
10,000-15,000 lbs.



AlphaPlow™
15,000-30,000 lbs.

FOR MACHINES WEIGHING
6,000 TO 30,000 LBS.

Model Number	FX-5.0	FX-6.0	FX-7.0	FX-8.0	Ultra-72	Ultra-84	Ultra-96	Ultra-108	Ultra-120	UltraXT-108	UltraXT-120	UltraXT-132	Alpha-10.0	Alpha-12.0	
Blade Width	5'	6'	7'	8'	6'	7'	8'	9'	10'	9'	10'	11'	10'	12'	
Blade Width at Full Angle	49.2"	59"	68.8"	78.6"	59"	68.8"	78.6"	88.5"	98.3"	88.5"	98.3"	114.6"	98.3"	118.0"	
Blade Height	30"	30"	30"	30"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	38"	38"	
Unit Weight (lbs.)	479	511	543	575	732	774	816	858	920	918	986	1,028	1,920	2,217	
Moldboard Gauge	12 Ga.	12 Ga.	12 Ga.	12 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	10 Ga.	
Trip Springs		2 Extension (4 Opt.)			4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	4 Ext	8 Ext	8 Ext	
Wear Shoes	Yes	Yes	Yes	Yes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	N/A	N/A	
Cutting Edge		1/2" x 6" Top Punch				5/8" x 6" Top Punch				5/8" x 6" Top Punch			3/4" x 8" Top Punch		
Angle Rams		1-1/2" x 10" Chrome				2" x 13" Nitro Steel				2" x 13" Nitro Steel			3" x 13" Nitro Steel Doubling Acting		
Vertical Ribs	4	4	4	4	6	6	6	6	8	6	6	8	8	10	
Moldboard Radius	15"	15"	15"	15"	14"	14"	14"	14"	14"	14"	14"	14"	19"	19"	
Full Down Pressure	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Floating / Full		
Spring Assist Down Pressure	Yes	Yes	Yes	Yes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	N/A	N/A	
Skid Steer Compatible		Standard				Standard				Standard			N/A	N/A	
Crossover Relief Valve	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Std.	Std.	Std.		Standard			Std.	Std.
SoftTouch™ Cutting Edge	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.		Optional			Opt.	Opt.
High Carbon Curb Guards	N/A	N/A	N/A	N/A	Opt.	Opt.	Opt.	Opt.	Opt.		Optional			N/A	N/A