

POWERED WING PLOWS

ApexPlowXT & HD Specifications



Model Number	APXT-8-14*	APHD-10-20	APHD-10-22	APHD-12-22	APHD-12-24
Blade Width	8'	10'	10'	12'	12'
Outside Width in Pusher Position	112" (9'4")	136" (11'4")	136" (11'4")	160" (13'4")	160" (13'4")
Maximum Width	175" (14'7")	245" (20'5")	269" (22'5")	269" (22'5")	293" (24'5")
Width in Backdrag Position	107" (8'11")	130" (10'10")	130" (10'10")	154" (12'10")	154" (12'10")
Width at Wide Angle	143" (11'11")	201" (16'9")	220" (18'4")	220" (18'4")	240" (20')
Width in Angled Narrow Position	99" (8'3")	122" (10'2")	122" (10'2")	141" (11'9")	141" (11'9")
Blade Height	36"	48"	48"	48"	48"
Unit Weight	2,800 lbs	4,700 lbs	4,900 lbs	5,000 lbs	5,200 lbs
Moldboard Gauge	10 Ga.	8 Ga.	8 Ga.	8 Ga.	8 Ga.
Trip Springs	2 Main + 2 per Wing	4 Main + 4 per Wing	4 Main + 4 per Wing	4 Main + 4 per Wing	4 Main + 4 per Wing
Moldboard Cutting Edge	3/4" x 8" Top Punch, High Carbon Standard (ActivEdge AR-400 or Carbide Optional)				
Angle Rams	10" x 2"	12" x 2"	12" x 2"	12" x 2"	12" x 2"
Vertical Ribs	6	6	6	8	8
Full Down Pressure	Yes	Yes	Yes	Yes	Yes
Crossover Relief Valve	Standard	Standard	Standard	Standard	Standard
Wing Thickness	5/16"	3/8"	3/8"	3/8"	3/8"
Wing Wear Shoes	AR-400, .75" + Tapered Front Curb-Jump Plate				
Wing Hinge Pin	1.5"	1.5"	1.5"	1.5"	1.5"
Wing Cylinder	1.5" x 6" (2 per Wing)	1.5" x 7.5" (2 per Wing)	1.5" x 7.5" (2 per Wing)	1.5" x 7.5" (2 per Wing)	1.5" x 7.5" (2 per Wing)

*Compatible with the Universal Skid Steer Mount.



SnowWolfPlows.com / 1.800.905.2265